

SDR 1404HD-5/1 4ch 5 in 1 Ultra HD Mini Video Recorder



- H.264
- AHD +TVI +CVI +Analog +IP
- ULTRA HD 4MPX AHD Cameras supported
- Compatible with 2.0 TVI and CVI cameras
- ONVIF
- Siera CLOUD
- 1 HDD
- SIERA DDNS
- HDMI
- 4G and WiFi modules (optional)
- PTZ control
- Mobile phone and Webserver viewer
- Video & Audio Editor
- Siera Panther CMS 3.0 for 192 cameras (Win/Mac)

Panther 3.0 / Designed for professional security applications. Ease setting interface. Special and ease interface for search, playback and backup. ULTRA HD resolution supported in all the channels. Remote viewing in: Win, Mac, iPhone, iPad, iPod, Android phones, Android tablets, Android device TV, etc. Free Siera DDNS. WiFi and 4G modules optional. Triple video outputs at the same time: BNC, VGA, HDMI. Silent system. Free 192 cameras CMS which support ULTRA HD resolutions.

Main Processor:	High Performance Embedded Microprocessor
Operation System:	Embedded Linux OS
Signal System:	PAL/NTSC
System Resource:	Pentaplex
Operation Interface:	Mouse
Video Split:	1/4/8
Video Resolution:	ANALOG/AHD/TVI/CVI: 4ch Ultra HD 4MPX (2688x1520) / 4ch 3MPX (2048x1536) 5 in 1: 4ch analog/AHD/TVI/CVI 1080p (1920x1080) + 4ch IP FULL HD1080p (1920x1080) 2ch analog/AHD/TVI/CVI Ultra HD 4MPX (2688x1520) + 2ch IP Ultra HD 4MPX (2688x1520) NVR: 8ch FULL HD (1920x1080) / 4ch 3MPX (2048x1536) / 4ch 5MPX (2560x1920)
Video Compression:	H.264
Image Control:	Configurable
Recording Speed:	PAL: 100 fps / NTSC: 120 fps
Motion Detection:	Configurable detection areas and Sensitivity
Audio Compression:	G.711
Recording Priority:	Manual > Motion Detection > Schedule
Playback Search:	Date, Time, Event, Channel
Smartphone app:	iSMS 5.0 (available in iOS and Android)
Video Storage:	HDD / Network
Backup Mode:	Network / USB / HDD
Video Input:	4 x BNC
Video Output:	VGA, HDMI
Audio Input:	4 x RCA
Audio Output:	1 x RCA
Ethernet Interface:	RJ45 100M/1000M Base-TX
PTZ Interface:	1 x RS485
USB Interface:	2 x USB2.0
4G and Wifi modules:	Supported (not included)
HDD/SATA Interface:	1 x SATA up to 6Tb
TCP/IP Ports:	80 / 3333 / 3334
UDP Ports:	37778 / 554
Power Supply:	DC12V±10% - 100 / 240VAC Power Adaptor Included
Power Consumption:	< 30W (HDD not included)
Working Temperature:	-10° C / +55° C
Working Humidity:	10% / 90%
Dimensions:	230 x 210 x 45 mm
Weight:	1,0 kg (HDD not included)

- H.264
- HDMI
- ULTRA HD
- PTZ
- AUDIO
- USB 2.0
- MOUSE
- MOBILE SURVEILLANCE
- NETWORK
- SIERA DDNS
- WARRANTY 2 YEARS

DATA SUBJECT TO CHANGE WITHOUT PRIOR NOTICE / SDR1404HD-1/5-0417