

SDR 1108HD-5/1 8ch 5 in 1 Mini Video Recorder



- H.264
- AHD +TVI +CVI +Analog +IP
- Compatible with 2.0 TVI and CVI Cameras
- **8ch Analog + 2ch IP Mode**
- ONVIF
- Siera CLOUD
- 1 HDD
- SIERA DDNS
- HDMI
- 4G and WiFi Modules (optional)
- PTZ Control
- Mobile Phone and Webserver Viewer
- Video & Audio Editor
- Siera Panther CMS 3.0 for 192 Cameras (Win/Mac)

Panther 3.0 / Designed for professional security applications. Ease setting interface. Special and ease interface for search, playback and backup. 720p/1080p resolution supported in all the channels. Remote viewing in: Win, Mac, iPhone, iPad, iPod, Android phones, Android tablets, Android device TV, etc. Free Siera DDNS. WiFi and 4G modules optional.

Double video outputs at the same time: VGA, HDMI. Silent system. Free 192 cameras CMS which support 1080p resolutions.

Main Processor: High Performance Embedded Microprocessor
 Operation System: Embedded Linux OS
 Signal System: PAL / NTSC
 System Resource: Pentaplex
 Operation Interface: Mouse
 Video Split : 1 / 4 / 8
 Video Resolution: ANALOG/AHD/TVI/CVI: 8ch 720P(1280 x 720) @17FPS/CH // 1080N (960 x 1080) @15FPS/CH // 8ch D1/960H (960x576)@30FPS 5 in 1: 8ch analog/AHD/TVI/CVI 1080N@30FPS/CH +2ch IP 1080P @30FPS/CH // 4ch Analog/AHD/TVI/CVI 1080N @30FPS/CH +4ch IP 1080P @30FPS/CH
 NVR: 8ch FULL 1080 HD (1920 x 1080) @30FPS/CH

Video Compression: H.264
 Image Control: Configurable
 Recording Speed: PAL: 200 fps / NTSC: 240 fps
 Motion Detection: Configurable Detection Areas and Sensitivity
 Audio Compression: G.711
 Recording Priority: Manual > Motion Detection > Schedule
 Playback Search: Date, Time, Event, Channel
 Smartphone app: iSMS 5.0 (available in iOS and Android)
 Video Storage: HDD / Network
 Backup Mode: Network / USB / HDD
 Video Input: 8 x BNC
 Video Output: VGA, HDMI
 Audio Input: 4 x RCA
 Audio Output: 1 x RCA
 Ethernet Interface: RJ45 100M/100M Base-TX
 PTZ Interface: 1 x RS485
 USB Interface: 2 x USB2.0
 4G and Wifi Modules: Supported (not included)
 HDD/SATA Interface: 1 x SATA up to 6Tb
 TCP/IP Ports: 80 / 3333 / 3334
 UDP Ports: 37778 / 554
 Power Supply: DC12V±10% - 100 / 240VAC Power Adaptor Included
 Power Consumption: < 30W (HDD not included)
 Working Temperature: -10° C / +55° C
 Working Humidity: 10% / 90%
 Dimensions: 230 x 210 x 45 mm
 Weight: 1,0 kg (HDD not included)

H.264

HDMI

720p
1080p

PTZ

AUDIO

USB 2.0

MOUSE

MOBILE SURVEILLANCE

NETWORK

SIERA DDNS

2 YR WARRANTY

DATA SUBJECT TO CHANGE WITHOUT PRIOR NOTICE / SDR1108HD-5/1-12/16