

SDR 1208HD-5/1

8ch. 5 in 1 Digital Video Recorder



- H.264
- AHD +TVI +CVI +Analog+IP
- Compatible with 2.0 TVI and CVI cameras
- **8ch Analog +2ch IP Mode**
- ONVIF
- 1 HDD
- Siera CLOUD
- SIERA DDNS
- HDMI
- 4G and WiFi modules (optional)
- PTZ control
- Mobile phone and Webserver viewer
- Video & Audio Editor
- Siera Panther CMS 3.0 for 192 cameras (Win/Mac)

Panther 3.0 / Designed for professional security applications. Ease setting interface. Special and ease interface for search, playback and backup. 720p/1080p resolution supported in all the channels. Remote viewing in: Win, Mac, iPhone, iPad, iPod, Android phones, Android tablets, Android device TV, etc. Free Siera DDNS. WiFi and 4G modules optional.

Double video outputs at the same time: VGA, HDMI. Silent system. Free 192 cameras CMS which support 1080p resolutions.

Main Processor:	High Performance Embedded Microprocessor
Operation System:	Embedded Linux OS
Signal System:	PAL / NTSC
System Resource:	Pentaplex
Operation Interface:	Mouse, Front Panel
Video Split:	1 / 4 / 8 / 9
Video Resolution:	ANALOG/AHD/TVI/CVI: 8ch HD 720P (1280x720) / 1080N (960x1080) @30FPS/CH, 8ch 960H (960x576)@30FPS/CH 5 in 1: 8ch analog/AHD/TVI/CVI 1080N@30FPS/CH +2ch IP 1080P@30FPS/CH 4ch analog/AHD/TVI/CVI 1080N @30FPS/CH +4ch IP 1080P @30FPS/CH 2ch analog/AHD/TVI/CVI 1080N @30FPS/CH +6ch IP 1080P @30FPS/CH NVR: 8ch FULL HD (1920 x 1080)@30FPS/CH 4ch 3 Megapixel (2048 1536)@30FPS/CH
Video Compression:	H.264
Image Control:	Configurable
Recording Speed:	PAL: 200 fps / NTSC: 240 fps
Motion Detection:	Configurable detection areas and Sensitivity
Audio Compression:	G.711
Recording Priority:	Manual > Motion Detection > Schedule
Playback Search:	Date, Time, Event, Channel
Smartphone app:	iSMS 5.0 (available in iOS and Android)
Video Storage:	HDD / Network
Backup Mode:	Network / USB / HDD
Video Input:	8 x BNC
Video Output:	VGA, HDMI
Audio Input:	4 x RCA
Audio Output:	1 x RCA
Ethernet Interface:	RJ45 100M/100M Base-TX
PTZ Interface:	1 x RS485
USB Interface:	2 x USB2.0
4G and Wifi modules:	Supported (not included)
HDD/SATA Interface:	HDD/SATA Interface: 1 x SATA up to 6Tb
TCP/IP Ports:	80 / 3333 / 34600
UDP Ports:	37778 / 554
Power Supply:	DC12V±10% - 100/240VAC Power Adaptor Included
Power Consumption:	< 30W (HDD not included)
Working Temperature:	-10° C / +55° C
Working Humidity:	10% / 90%
Dimensions:	250 x 225 x 45 mm
Weight:	1,2 kg (HDD not included)

- H.264
- HDMI
- 720p
1080p
- PTZ
- AUDIO
- USB 2.0
- MOUSE
- MOBILE SURVEILLANCE
- NETWORK
- SIERA DDNS
- 2 YEAR WARRANTY