



# TSC-NVR-L9364PN

20009



<b>Main Processor</b>	ARM Cortex A17 Quad-core Processor
<b>Operating System</b>	Embedded LINUX
<b>IP Camera Input</b>	64 Channel, Support 4096×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc
<b>Incoming Bandwidth</b>	300Mb
<b>Output</b>	1 VGA, 2 HDMI
<b>Video Compression</b>	H.264/H.265
<b>Recording Resolution</b>	4k(4096×2160),5MP(2592×1944), 4MP(2688×1520),3MP(2048×1536), 1080P(1920×1080),960P(1280×960), 720P(1280×720),D1(704×576/704×480) (All real time)
<b>Record Rate</b>	NTSC: 4k@30×30fp,5MP@45×30fp,4MP@64×30fp,3MP@60×30fp,1080P@64×30fp, 960P@64×30fp, 720P@64×30fp, D1@64×30fp
<b>Preview Resolution</b>	Multi-channels@Main Stream/Sub-stream
<b>Playback Resolution</b>	4CH@4K
<b>Search Mode</b>	ALL, Channel, Manual, Time, Date, Motion Detection
<b>Playback Functions</b>	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
<b>Trigger Events</b>	Recording, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips, Alarm output
<b>Motion Detection</b>	64 Channels, MD Zones: 396 (22 × 18)

<b>Alarm Input/Output</b>	16CH Input/4CH Output
<b>Audio Input/Output</b>	1CH RCA Input/1CH RCA Output
<b>Network Interface</b>	2xRJ-45 10/100/1000Mbps Self-adaptive Ethernet Interfaces
<b>Network Functions</b>	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
<b>Onvif</b>	Support ONVIF 2.4
<b>Cloud Support(P2P)</b>	Yes
<b>RS485</b>	1 Port, for PTZ Control
<b>CMS Software</b>	Support Windows 7/ 8/10
<b>IE Brower</b>	IE6-11, Google Chrome(IE Tab), Firefox (IE Tab)
<b>Smart Phone</b>	iPhone, iPad, Android, Android Pad
<b>Remote View</b>	Support Remote View by Smart Phone
<b>Hard Disk Driver</b>	8 SATA Hard Disk Interface(Up to 48TB) + 1 eSATA interface
<b>Backup</b>	2xUSB2.0 Interface,1xUSB3.0 Interface
<b>Power/Current</b>	100 to 240 VAC, 50 to 60 Hz
<b>Dimension (mm)</b>	2U 440(W) x 450(D) x 95(H)
<b>Weight (Kg)</b>	9.8 (without HDD)
<b>Working Environment</b>	-10~+55℃ RH10%-90% MAX