



# TSC-IR25HTC500FS

31001

|   |  |
|---|--|
| <b>Image Sensor</b>                     | 1/2.9" SONY 6MP Starvis Back-illuminated CMOS sensor |
| <b>Effective Picture Elements (H×V)</b> | 5MP: 2592(H)×1944(V); 4MP: 2560(H)*1440(V)           |
| <b>Horizontal Resolution</b>            | 5MP  |
| <b>Video Output</b>                     | AHD 5M/ TVI 5M/ CVI 4M/ CVBS                         |
| <b>Minimum Illumination</b>             | 0.01 Lux /F2.0                                       |
| <b>S/N Ratio</b>                        | More than 50dB                                       |
| <b>Synchronous System</b>               | Internal   |
| <b>Electronic Shutter</b>               | 1/25s~1/50,000s , 1/30s~1/60,000s                    |
| <b>Gama Characteristic</b>              | 0.45   |
| <b>IR Distance</b>                      | 30 meters with 42μ x 2PCS Infrared LED               |
| <b>IR Status</b>                        | Under 10 Lux by CDS                                  |
| <b>IR Power On</b>                      | CDS Motor Control                                    |
| <b>OSD/ UTC Support</b>                 | Yes  |
| <b>Other Functions</b>                  | DWDR, 3DNR, IR-Cut, Auto Gain Control, White Balance |
| <b>Power/Current</b>                    | DC12V(+/-10%)/600mA                                  |
| <b>Lens</b>                             | Board Lens 2.8mm                                     |
| <b>Housing</b>                          | IP66   |
| <b>Dimension (mm)</b>                   | 157(W) x 70(H) x 66(D)                               |
| <b>Weight (g)</b>                       | 650  |
| <b>Storage Temperature</b>              | -30~+60℃ RH95% MAX                                   |
| <b>Operating Temperature</b>            | -10~+50℃ RH95% MAX                                   |