



TSC-IPDOV30H200W

20221



| | |
|-----------------------------------|---|
| Image Sensor | 1/2.9" SONY Low Illumination CMOS Sensor |
| Main processor | HI3516CV300 |
| Effective Picture Elements | 1985(H)*1105(V) |
| Horizontal Resolution | 2 Megapixeles (1080P) |
| Video Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG |
| Minimum Illumination | 0.01 Lux |
| S/N Ratio | More than 52dB |
| Electronic Shutter Time | 1/25s~1/10,000s |
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP, DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,SMTP |
| Onvif | Support ONVIF 2.4 |
| P2P | YES, Support QR Code |
| Antena | 3dbi |
| Wifi | Wi-Fi(IEEE802.11b/g/n) |
| Wifi Range | No obstacles 300m Max. |
| SD Card Slot | Support 128G Micro SD |
| Main Stream | 1920*1080@25fps/1280*720@25fps |
| Sub Stream | 720*480@25fps |
| Tri Stream | 352*288@25fps |

| | |
|----------------------------------|---|
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari |
| Smart Phone | iPhone, iPad, Android, Android Pad |
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast / Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| Defog Mode, ROI, BLC, WDR | Support |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/NAS/CMS/Web |
| IR Distance | 30 M with 14μ x 24PCS Infrared LED |
| IR Status | Under 10 Lux By CDS |
| IR Power On | CDS Auto Control |
| Auto Gain Control | Auto |
| Power/Current | DC12V(+/-10%)/500mA |
| Lens | 2.8-12mm Manual Zoom Lens |
| Housing | Plastic |
| Dimension (mm) | Φ120 x 104(H) |
| Weight (g) | 600 |
| Storage Temperature | -20~+60℃ RH95% MAX |
| Operating Temperature | -20~+60℃ RH95% MAX |