



TSC-IPIR25H400

20033



| | |
|-----------------------------------|---|
| Image Sensor | 1/3" OV High-resolution CMOS Sensor OV4689 |
| Main processor | Hi3516D |
| Effective Picture Elements | 2688H)*1520(V) |
| Horizontal Resolution | 4 Megapixeles (4MP) |
| Video Compression | H.264/H.265 |
| Video Output | IP |
| Minimum Illumination | 0.01 Lux |
| S/N Ratio | More than 52dB |
| Electronic Shutter Time | 1/25s~1/10,000s |
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP, DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,SMTP |
| Onvif | Support ONVIF 2.4 |
| P2P | YES, Support QR Code |
| PoE & SD Card Slot | Internal PoE, Support 64G Max |
| Main Stream 1 | 2560*1440@20fps |
| Main Stream 2 | 2304*1296@30fps |
| Main Stream 3 | 1920*1080@30fps/1280*720@30fps |
| Sub Stream | 720*480@20fps or 30fps |
| Tri Stream | 352*288@25fps |
| IE Brower | IE8-11, Google Chrome, Firefox, Safari, Mac Safari |
| Smart Phone | iPhone, iPad, Android, Android Pad |

| | |
|------------------------------|---|
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast / Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| Corridor Pattern | Support |
| Defog Mode | Support |
| BLC, WDR | Support |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/NAS/CMS/Web |
| IR Distance | 30 meters with 42μ x 2PCS Infrared LED |
| IR Status | Under 10 Lux By CDS |
| IR Power On | CDS Auto Control |
| Auto Gain Control | Auto |
| Power/Current | DC12V(+/-10%)/600mA |
| Lens | 2.8mm Lens |
| Housing | IP66 |
| Dimension (mm) | 157(W) x 70(H) x 66(D) |
| Weight (g) | 650 |
| Storage Temperature | -20~+60℃ RH95% MAX |
| Operating Temperature | -20~+60℃ RH95% MAX |